



## Plattenmagnet

Magnetkern Hartferrit, Einsatztemperatur max. 150 °C

Maße in mm			Gewinde M	Lochabstand mm	Art.-Nr.
L	B	H			
145 <sup>+2/-2</sup>	105 <sup>+2/-2</sup>	50 <sup>+2/-2</sup>	2 × M8 × 8	100	48.560
210 <sup>+2/-2</sup>	105 <sup>+2/-2</sup>	50 <sup>+2/-2</sup>	2 × M8 × 8	100	48.561
280 <sup>+2/-2</sup>	105 <sup>+2/-2</sup>	50 <sup>+2/-2</sup>	2 × M8 × 8	200	48.562
310 <sup>+2/-2</sup>	105 <sup>+2/-2</sup>	50 <sup>+2/-2</sup>	2 × M8 × 10	200	48.563
410 <sup>+2/-2</sup>	105 <sup>+2/-2</sup>	50 <sup>+2/-2</sup>	3 × M8 × 8	150	48.565
610 <sup>+2/-2</sup>	105 <sup>+2/-2</sup>	50 <sup>+2/-2</sup>	4 × M8 × 8	150	48.568
765 <sup>+2/-2</sup>	105 <sup>+2/-2</sup>	50 <sup>+2/-2</sup>	4 × M8 × 8	200	48.569

Magnetkern NdFeB, Einsatztemperatur max. 80 °C

Maße in mm			Gewinde M	Lochabstand mm	Art.-Nr.
L	B	H			
176 <sup>+2/-2</sup>	104 <sup>+2/-2</sup>	41,5 <sup>+2/-2</sup>	2 × M8 × 20	100	48.760
260 <sup>+2/-2</sup>	104 <sup>+2/-2</sup>	41,5 <sup>+2/-2</sup>	2 × M8 × 20	150	48.762
302 <sup>+2/-2</sup>	104 <sup>+2/-2</sup>	41,5 <sup>+2/-2</sup>	2 × M10 × 20	200	48.763
386 <sup>+2/-2</sup>	104 <sup>+2/-2</sup>	41,5 <sup>+2/-2</sup>	2 × M10 × 20	250	48.765
470 <sup>+2/-2</sup>	104 <sup>+2/-2</sup>	41,5 <sup>+2/-2</sup>	2 × M10 × 20	350	48.767