



MaxX-Lasthebemagnete

Müheloses Transportieren von ferromagnetischen Lasten, für Flach- und Rundmaterial

Maße in mm										Modell	Gewicht kg	Haftkraft max. kg	Stärke min. mm	Länge max. mm	Haftkraft max. kg	Stärke min. mm	Länge max. mm	Ø max. mm	Art.-Nr.
A	B	C	D	E	F	G	H	I	L										
121	76	79	79	66	30	44	145	132	137	MaxX 125	3,7	125	20	1.000	50	10	1.000	300	41.209
189	143	79	79	63	35	43	142	130	137	MaxX 250	6	250	20	1.500	100	10	1.500	300	41.210
250	199	106	101	88	52	60	189	165	170	MaxX 500	15	500	25	2.000	200	15	2.000	400	41.211
342	284	133	131	88	52	60	219	225	240	MaxX 1000	36	1.000	40	3.000	400	25	3.000	450	41.212
383	316	166	171	122	64	87	293	330	377	MaxX 1500	66	1.500	45	3.000	600	30	3.000	500	41.213
457	390	166	171	122	64	87	293	330	377	MaxX 2000	80	2.000	55	3.000	800	35	3.000	600	41.214
189	143	79	79	63	35	43	142	130	137	MaxX 300 E	6	300	20	1.500	150	10	1.500	300	41.220
250	199	106	101	88	52	60	189	165	170	MaxX 600 E	15	600	25	2.000	250	15	2.000	400	41.221
189	170	79	87	63	35	43	150	130	137	MaxX TG 150	6	150	8	1.500	60	8	1.500	240	41.315
250	230	106	101	88	52	60	189	165	170	MaxX TG 300	16	300	10	2.000	120	10	2.000	290	41.330

Flachmaterial

Rundmaterial