



Magnetsystem flach, Magnetkern NdFeB

Metallgehäuse verzinkt, Einsatztemperatur max. 80 °C

Maße in mm		Gewicht	Haftkraft*	Art.-Nr.
D	L	g	N	
6 ^{+0,1} / _{-0,1}	4,5 ^{+0,1} / _{-0,1}	1	5	38.200
8 ^{+0,1} / _{-0,1}	4,5 ^{+0,1} / _{-0,1}	2	13	38.201
10 ^{+0,1} / _{-0,1}	4,5 ^{+0,1} / _{-0,1}	2,5	25	38.202
13 ^{+0,1} / _{-0,1}	4,5 ^{+0,1} / _{-0,1}	4	60	38.203
16 ^{+0,1} / _{-0,1}	4,5 ^{+0,1} / _{-0,1}	6	95	38.204
20 ^{+0,1} / _{-0,1}	6 ^{+0,1} / _{-0,1}	14	140	38.205
25 ^{+0,1} / _{-0,1}	7 ^{+0,2} / _{-0,2}	25	200	38.206
32 ^{+0,1} / _{-0,1}	7 ^{+0,2} / _{-0,2}	41	350	38.207

* Erläuterungen zur Haftkraft finden Sie auf Seite 25.